

LOW PRESSURE SINGLE STAGE LP GAS REGULATORS (GR-800)

Applications:

The model GR-800 regulator incorporates a drip lip vent and is ideally suited for use with portable appliances.

Specifications

- Zinc Die Cast
- Molded Rubber Diaphragms
- Underwriters Laboratories Listed
- Integral Pressure Relief



PART No.	Inlet	Outlet	Vent Position	Capacity BTU/Hr* Propane
GR-800	1/4 FPT	3/8 FPT	Drip Lip Vent Above Outlet	175,000 BTU/Hr*
GR-856	GR-800 regulator with Hard nose P.O.L.			
GR-866	GR-800 regulator with QCC1 (1-5/16 F. Acme)			
GR-876	GR-800 regulator with Soft nose P.O.L.			

*Based on 25 PSIG inlet pressure and 9" W.C. outlet pressure at Manufacturer's set point.
Manufacturer's set point = 100 PSIG and 11" W.C. outlet at 50 SCFH propane.

NOTE:
FOR INFORMATION ON ORDERING
COMPLETE HOSE ASSEMBLY
I6C**FS6MP6, I6TC**FS6MP6
SEE PAGE: 143

FLOW CHARACTERISTIC CHART FOR
MODEL GR-800

