

LOW PRESSURE TWO-STAGE AUTOMATIC CHANGEOVER REGULATORS (GR-9994)

Applications: The Fairview **X-SERIES** * Compact Automatic Changelogover Regulator redirects LP gas vapor flow from an empty designated service cylinder to a reserve cylinder, without interruption of service. It features a green indicator dome which changes to red when the service cylinder needs to be refilled.

Specifications

- Excess Flow
- Zinc Die Cast
- Molded Rubber Diaphragms
- CSA Listed to U.L. 144
- 2nd Stage Relief Mechanism Per U.L. 144
- Powder Coated



Measures
6-1/4 (IN.) high.

PART No.	Inlets (Back Check Incl.)	Outlet	Capacity BTU/Hr* Propane
GR-9994	1/4 F. Inv. Flare	3/8 FPT	Service: 262,500 BTU/Hr* Reserve: 210,00 BTU/Hr*
GR-9994-U	GR-9994 with GR-RVB Mounting Bracket		
GR-9994-1Z	GR-9994 with GR-900 Mounting Bracket		
GR-9984-KIT-1	GR-9994 with Type I QCC1 12 Inch assembly (x2)		
GR-900	Z Mounting Bracket		
GR-RVB	RV Style Mounting Bracket		
GR-5994	Protective Cover		



GR-5994



GR-900



GR-RVB

*Based on 25 PSIG inlet pressure and 9" W.C. outlet pressure at Manufacturer's set point. Manufacturer's set point = 100 PSIG and 11" W.C. outlet at 40 SCFH propane.

FLOW CHARACTERISTIC CHART FOR
MODEL GR-9984 AND GR-9984XF

