

GAS~FLO® NATURAL GAS GRILL / B.B.Q. HOSE ASSEMBLIES (

Applications: Used To Conduct Natural Gas And Propane In A Gaseous State.

3/8" TYPE I HOSE WITH GAS~FLO® QUICK DISCONNECT

RUBBER - Hose Approved to C.G.A. Standard 8.1
Capacity Natural Gas. Q.D. Rated to 1/2 PSIG



Assemblies come complete with dust plug and cap. Remove "PC" if not required.



Retail packaging available suffix PART No. with "PS".



PART No.	Hose I.D. (IN.)	Description	Coupler (IN.)	Nipple (IN)	Length (IN.)	BTU /Hr.
I6C120FS6QDPC	3/8	3/8" F. S.A.E. X 3/8" Quick Disconnect	3/8	3/8	120"	71,208
I6C144FS6QDPC	3/8	3/8" F. S.A.E. X 3/8" Quick Disconnect	3/8	3/8	144"	65,016
I6C180FS6QDPC	3/8	3/8" F. S.A.E. X 3/8" Quick Disconnect	3/8	3/8	180"	51,858

3/8" GREY HOSE WITH GAS~FLO® 3/8" QUICK DISCONNECT

CSA Certified to Standard ANSI Z21.54 C.G.A. 8.4 (Thermoplastic)
Used To Conduct Natural Gas / Propane In A Gaseous State Up To 1/2 P.S.I. 80,000 BTU/Hr. Capacity Natural Gas



Assemblies come complete with dust plug and cap. Remove "PC" if not required.



Retail packaging available suffix PART No. with "PS".



PART No.	Hose I.D. (IN.)	Description	Coupler (IN.)	Nipple (IN)	Length (IN.)	BTU /Hr.
I6NGTC120FS6QDPC	3/8	3/8" F. S.A.E. Swivel X 3/8" Quick Disconnect	3/8	3/8	120"	80,000
I6NGTC144FS6QDPC	3/8	3/8" F. S.A.E. Swivel X 3/8" Quick Disconnect	3/8	3/8	144"	80,000
I6NGTC180FS6QDPC	3/8	3/8" F. S.A.E. Swivel X 3/8" Quick Disconnect	3/8	3/8	180"	80,000

TO BE INSTALLED BY LICENSED GAS FITTERS ONLY.